



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

<b>Product name</b>	<b>Never-Seez Reg NSA16 Aerosol</b>
<b>MSDS name</b>	Never-Seez Regular Grade Aerosol
<b>Product name(s) covered</b>	See Section 16 for Product Names Covered.
<b>CAS #</b>	Mixture
<b>Product use</b>	Lubricants
<b>Generic description</b>	Aerosol Spray Flammable
<b>Manufacturer</b>	Bostik, Inc. 11320 Watertown Plank Rd Wauwatosa, WI 53226 USA
<b>24 hour emergency assistance</b>	Telephone: 1-800-227-0332 (Outside U.S.) 1-703-527-3887
<b>General assistance</b>	Telephone: 1-800-843-0844
<b>MSDS assistance</b>	Telephone: 1-800-843-0844

## 2. Hazards Identification

<b>Emergency overview</b>	Contact with this material can cause irritation to the skin, eyes and mucous membranes. Product is a flammable aerosol. Pressurized container may explode when exposed to heat or flame. May be harmful by inhalation, ingestion, skin adsorption.
<b>Potential health effects</b>	
<b>Eyes</b>	Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause irreversible eye damage.
<b>Skin</b>	This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin. Rapid evaporation of the liquid may cause frostbite.
<b>Inhalation</b>	This product may cause irritation to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination. High concentration of vapours may induce unconsciousness.
<b>Ingestion</b>	This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
<b>Target organs</b>	Respiratory system. Eyes. Skin. Central nervous system.
<b>Signs and symptoms</b>	Signs and symptoms of overexposure to this product include headache, irritation of upper respiratory tract, asthmatic symptoms, chest tightness, breathing difficulty, coughing, eye irritation, skin irritation, diarrhea.

## 3. Composition / Information on Ingredients

<b>Hazardous components</b>	<b>CAS #</b>	<b>Percent</b>
Heptane	142-82-5	15 - 40
Acetone	67-64-1	7 - 13
Propane	74-98-6	7 - 13
Copper Powder	7440-50-8	1 - 5
Aluminum	7429-90-5	0.1 - 1

## 4. First Aid Measures

<b>First aid procedures</b>	
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
<b>Skin contact</b>	For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
<b>Inhalation</b>	Move person to non-contaminated air. Call a physician if symptoms develop or persist.

**Ingestion**

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

**Notes to physician**

This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately. If overexposure to the solvents in this product is suspected, testing should include nervous system and brain effects including recent memory, mood, concentration, headaches and altered sleep patterns. Liver and kidney function should be evaluated.

## 5. Fire Fighting Measures

**Extinguishing media****Suitable extinguishing media**

Dry chemical, foam, carbon dioxide. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools; this may result in frothing and increase fire intensity.

**Basic fire fighting procedures**

DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Pressurized Container: May explode when exposed to heat or flame. Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.

**Fire fighting equipment/instructions**

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

**Sensitivity to static discharge**

Sparks generated by static discharge may ignite this product or its vapors. All containers and equipment must be bonded or grounded to minimize risk.

**Unusual fire & explosion hazards**

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water.

**Flash point**

-156 °F (-104.4 °C)

## 6. Accidental Release Measures

**Emergency action**

Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate protective equipment and clothing during clean-up.

**Environmental precautions**

Prevent further leakage or spillage if safe to do so.

**Containment procedures**

Eliminate sources of ignition. Stop the flow of material, if this is without risk. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers.

**Reporting**

See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

## 7. Handling and Storage

For Commercial Use Only - Not Packaged or Labeled for Home Use!

**Handling**

Keep this product from heat, sparks, or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing mists or aerosols of this product. Use this product with adequate ventilation. Do not reuse the empty container.

**Storage**

Store in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from direct sunlight. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

**Empty container precaution**

Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

## 8. Exposure Controls / Personal Protection

**Engineering controls**

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Explosion proof exhaust ventilation should be used. Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended exposure limits.

## Personal protective equipment

<b>Eye protection</b>	Wear safety glasses with side shields.
<b>Skin and body protection</b>	Impervious gloves should be used at all times when handling this product. Recommended gloves include rubber, neoprene, nitrile or viton. Use of protective coveralls and long sleeves is recommended.
<b>Respiratory protection</b>	Do not inhale aerosol. In case of insufficient ventilation wear suitable respiratory equipment. Special applications may necessitate the use of more stringent respiratory protection equipment.

**General** Eyewash fountains and emergency showers are required.

## Additional exposure data

### US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m<sup>3</sup> & ppm

Acetone	67-64-1	ACETONE 500 PPM
---------	---------	-----------------

### US NIOSH Pocket Guide to Chemical Hazards: Ceiling Limit Value and Time Period (if specified)

Heptane	142-82-5	N-HEPTANE 1800 MGM3 - 440 PPM 15-min
---------	----------	--------------------------------------

### US OSHA Table Z-1-A: Time Weighted Average (TWA): mg/m<sup>3</sup> & ppm

Heptane	142-82-5	HEPTANE (N-HEPTANE) 1600 MGM3 - 400 PPM
---------	----------	---

Acetone	67-64-1	ACETONE 1800 MGM3 - 750 PPM
---------	---------	-----------------------------

Propane	74-98-6	PROPANE 1800 MGM3 - 1000 PPM
---------	---------	------------------------------

## 9. Physical & Chemical Properties

<b>Target solids</b>	40 %
<b>pH</b>	N/A
<b>Density</b>	0.789 g/cc
<b>Odor</b>	Grease-like
<b>Color</b>	Dark Gray
<b>Physical state</b>	Aerosol
<b>Freeze protect</b>	No
<b>VOC (Volatile Organic Compounds)</b>	50 %

## 10. Chemical Stability & Reactivity Information

<b>Hazardous reactions/decomposition products</b>	Upon decomposition, this product may yield oxides of nitrogen and ammonia, carbon dioxide, carbon monoxide and other low molecular weight hydrocarbons.
<b>Hazardous polymerization</b>	Will not occur.
<b>Conditions to avoid</b>	Keep away from sources of ignition. Avoid contact with Strong Oxidizers, Reducers, Acids and Alkalis.
<b>Stability</b>	Stable under normal conditions.

## 11. Toxicological Information

<b>Chronic effects</b>	Chronic exposure to solvents can cause reproductive problems, reduced fertility, dryness and cracking of skin, headaches, loss of appetite and nausea.
<b>Carcinogenicity</b>	If this product contains any carcinogens, they will be noted below:

## 12. Ecological Information

<b>Ecotoxicological information</b>	Organic solvents produce slight to moderate toxicity to aquatic life. Insufficient data exists to evaluate the effect on plants, birds or land animals.
-------------------------------------	---

## 13. Disposal Considerations

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

<b>Waste disposal</b>	Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.
-----------------------	---

## 14. Transport Information

### DOT

**Basic shipping requirements:**

**Proper shipping name** Consumer Commodity  
**Hazard class** ORM-D

### IATA

**Basic shipping requirements:**

**Proper shipping name** Aerosols, Flammable (each not exceeding 1 L capacity)  
**Hazard class** 2.1  
**UN number** 1950



### IMDG

**Basic shipping requirements:**

**Proper shipping name** Aerosols, Flammable, (each not exceeding 1 L capacity)  
**Hazard class** 2.1  
**UN number** 1950  
**Marine pollutant** Copper Powder



## 15. Regulatory Information

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200

The product(s) covered by this M(SDS) do not include any of the substances above a concentration of 0.1% weight by weight (w/w) in the Candidate List of Substances of Very High Concern (SVHC) for authorization published or proposed by ECHA as follows: the list of 15 substances for authorization published on October 28, 2008, the list of 15 substances proposed on August 31, 2009, the list of 14 substances proposed on January 13, 2010, the list of 8 substances proposed on March 8, 2010, the list of 8 substances proposed on June 18, 2010, the list of 11 substances proposed on October 14, 2010 and the list of 8 substances proposed on December 15, 2010.

**Federal regulations** All components are on the U.S. EPA TSCA Inventory List.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Aluminum	7429-90-5	ALUMINUM (FUME OR DUST) US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance
Copper Powder	7440-50-8	COPPER US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

**US TSCA Section 12(b) Export Notification: Export Notification requirement/De minimis concentration**

Heptane	142-82-5	N-HEPTANE
---------	----------	-----------

**State regulations**

If this product contains any California Proposition 65 chemicals at reportable levels they will be listed below:

**International regulations**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

All components are included on the Canadian Domestic Substances List (DSL).

**HMIS Ratings**

Health: 2\*  
Flammability: 4  
Physical hazard: 0  
Personal protection: X

**SARA 311/312 HAZARD CATEGORIES**

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**WHMIS status**

Controlled

**WHMIS labeling****WHMIS classification**

A - Compressed Gas  
B5 - Flammable/Combustible  
D2A - Other Toxic Effects-VERY TOXIC  
D2B - Other Toxic Effects-TOXIC

**16. Other Information****Product name(s) covered**

BNRG12AC12 - REGULAR GRADE 12/12OZ AERO C  
V056260 - NEV-SZ REG NSA16 12.5OZ AERO

**Disclaimer**

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

**Further information**

If there are any characters following an individual item number, they are just designations for the various types of packaging that are available for this product. For example, a product "G12345-XX" is item number "G12345" with a packaging designation of "XX". These characters do not indicate a different product nor a different regulatory, health, safety and/or environmental status. This document covers the item numbers listed above for all of their packaging types.

**Issue date**

05/13/2011

**Prepared by**

Bostik, Inc. Regulatory Affairs

**Supercedes**

11/12/2010

**This data sheet contains changes from the previous version in section(s):**

First Aid Measures: Notes to physician  
Regulatory Information: International regulations  
Regulatory Information: Default Statements  
Other Information: Further information