

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier : **LIQUID WRENCH LUBRICANT**

Product Use : Lubricant

Chemical Family : Mixture.

Manufacturer part no. : L212C

Supplier's name and address:
Radiator Specialty Co., of Canada
 1711 Aimco Blvd.
 Mississauga, ON, Canada
 L4W 1H7

Manufacturer's name and address:
 Refer to Supplier

Information Telephone # : (905) 625-9117 (Monday - Friday, 9AM - 5PM)

24 Hr. Emergency Tel # : 613-996-6666 (CANUTEC)

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR).
 WHMIS classification:
 Class A (Pressurized containers);
 Class B5 (Flammable Aerosols);
 Class D1A (Materials Causing Immediate and Serious Toxic Effects, Very Toxic Material);
 Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material);
 Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

Labelling: Phrases recommended to appear on a supplier label, can be found in Section 15. WHMIS symbols required on a supplier label:



Emergency Overview : Light yellow to brown liquid. Aerosol spray. Vanilla odour. **WARNING!** Flammable aerosol. Contents under pressure. Container may explode if heated. **POISON!** May be fatal if inhaled. Harmful or fatal if absorbed through the skin. May cause nausea, vomiting, headache and other central nervous system effects. May be harmful if swallowed. May be an aspiration hazard. Can enter the lungs and cause damage. May cause respiratory irritation. Causes skin and eye irritation. Contains material which can cause damage to the blood system, the liver and the kidneys. Possible birth defect hazard - contains material that may cause birth defects, based on animal data. Possible cancer hazard - contains material which may cause cancer.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

- Inhalation** : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Inhalation in very high concentrations may result in blood system effects, such as red blood cell fragility. Liver and kidney injuries may occur. May result in unconsciousness and possibly death.
- Skin** : May cause moderate to severe skin irritation. May be absorbed and cause symptoms similar to those for inhalation. If product is sprayed directly on skin, symptoms of frostbite may be experienced including numbness, pricking and itching.
- Eyes** : May cause moderate to severe irritation. If product is sprayed directly into the eyes, could cause freezing of the eye.
- Ingestion** : Not an expected route of entry under normal conditions of use. However, if the product is sprayed directly into mouth and large amounts of the liquid concentrate are swallowed, it may cause irritation to the mouth, throat and stomach. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Ingestion may cause symptoms similar to inhalation. May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Effects of long-term (chronic) exposure

: Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood.

Carcinogenic status

: Possible cancer hazard. See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards

: May cause birth defects. See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
Hydrotreated heavy naphthenic distillate	64742-52-5	30.00 - 60.00
Petroleum hydrocarbon	8052-41-3	30.00 - 60.00
1,2,4-Trimethylbenzene	95-63-6	1.00 - 5.00
2-butoxyethanol	111-76-2	1.00 - 5.00
Carbon dioxide	124-38-9	1.00 - 5.00
1,3,5-Trimethylbenzene	108-67-8	1.00 - 5.00
Xylene	1330-20-7	1.00 - 5.00

SECTION 4 - FIRST AID MEASURES**Inhalation**

: Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.

Skin contact

: Remove/Take off immediately all contaminated clothing. Wash exposed area thoroughly with soap and water for at least 15 minutes. Obtain medical attention immediately.

Eye contact

: Immediately flush eyes with plenty of water for at least 15 minutes. Seek immediate medical attention/advice.

Ingestion

: Seek immediate medical attention/advice. Do not induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.

Notes For Physician

: Treat symptomatically. This product is a CNS depressant.

SECTION 5 - FIRE FIGHTING MEASURES**Fire hazards/conditions of flammability**

: Flammable aerosol. Will ignite when exposed to heat, flame and other sources of ignition. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time. Product may float, and be re-ignited at the water's surface.

Oxidizing properties

: None known.

Explosion data: Sensitivity to mechanical impact / static discharge

: Aerosols are sensitive to mechanical impact. Contents under pressure. May be sensitive to static discharge.

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Shield personnel to protect from venting or rupturing containers. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

: Carbon oxides; nitrogen oxides (NOx); Sulphur oxides; Phosphorus compounds; Polycyclic aromatic hydrocarbons; other unidentified organic compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up.
- Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.
- Spill response/cleanup** : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. No sparking tools should be used. Avoid contact with incompatible materials. Do not puncture or incinerate. Wash thoroughly after handling.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area. No smoking in the area.
- Incompatible materials** : Strong oxidizing agents; Acids; Bases; Reactive metals.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Hydrotreated heavy naphthenic distillate	5 mg/m ³ (As 'Oil mist, mineral')	N/Av	5 mg/m ³ (As 'Oil mist, mineral')	N/Av
Petroleum hydrocarbon	100 ppm	N/Av	500 ppm	N/Av
1,2,4-Trimethylbenzene	*25 ppm	N/Av	*25 ppm (final rule limit)	N/Av
2-butoxyethanol	20 ppm	N/Av	50 ppm (skin)	N/Av
Carbon dioxide	5000 ppm	30,000 ppm	5000 ppm	N/Av
1,3,5-Trimethylbenzene	*25ppm	N/Av	*25ppm (final rule limit)	N/Av
Xylene	100 ppm	150 ppm	100 ppm	N/Av

*Note: The OSHA PEL's and ACGIH TLV's listed above for 1,2,4-Trimethylbenzene and 1,3,5-Trimethylbenzene are for 'Trimethylbenzene (mixed isomers)'.

- Ventilation and engineering measures** : Use in a well-ventilated area. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.
- Respiratory protection** : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.
- Skin protection** : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.
- Eye / face protection** : Chemical splash goggles are recommended.
- Other protective equipment** : Depending on conditions of use, an impervious apron should be worn. An eyewash station and safety shower should be made available in the immediate working area.
- General hygiene considerations** : Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink, smoke or use cosmetics while working with this product. Remove and wash contaminated clothing before re-use. Wash with soap and water after handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : Liquid aerosol. **Appearance** : Light yellow to brown liquid.

Odour	: Vanilla odour.	Odour threshold	: N/Av
pH	: N/Av		
Boiling point	: > 149°C (concentrate)	Specific gravity	: 0.85 @ 20°C
Melting/Freezing point	: N/Av	Coefficient of water/oil distribution	: N/Av
Vapour pressure (mmHg @ 20° C / 68° F)	: N/Av	Solubility in water	: Insoluble.
Vapour density (Air = 1)	: N/Av	Evaporation rate (n-Butyl acetate = 1)	: N/Av
Volatile organic Compounds (VOC's)	: N/Av	Volatiles (% by weight)	: < 50%
Flash point	: 39°C (concentrate)		
Flash point Method	: TCC	Auto-ignition temperature	: Not available.
Lower flammable limit (% by vol.)	: N/Av	Upper flammable limit (% by vol.)	: N/Av
Flame Projection Length	: 15 - 100 cm	Flashback observed	: N/Av
Absolute pressure of container	: N/Av	Viscosity	: N/Av
General Information	: No additional information.		

Section 10: STABILITY AND REACTIVITY

Stability and reactivity	: Stable under the recommended storage and handling conditions prescribed.
Hazardous polymerization	: Hazardous polymerisation does not occur.
Conditions to avoid	: Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas.
Materials To Avoid And Incompatibility	: See Section 7 (Handling and Storage) for further details.
Hazardous decomposition products	: None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs	: Eyes, skin, respiratory system, central nervous system, blood system, liver, brain and kidneys.
Routes of exposure	: <i>Inhalation</i> : YES <i>Skin Absorption</i> : YES <i>Skin & Eyes</i> : YES <i>Ingestion</i> : YES
Irritancy	: May cause moderate to severe skin and eye irritation.
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

Ingredients	LC₅₀(4hr)	LD₅₀	
	inh, rat	(Oral, rat)	(Rabbit, dermal)
Hydrotreated heavy naphthenic distillate	2180mg/m ³ (mist)	> 5000 mg/kg	> 2000 mg/kg
Petroleum hydrocarbon	> 5500 mg/m ³	> 5000 mg/kg	> 3000 mg/kg
1,2,4-Trimethylbenzene	18,000 mg/m ³	5000 mg/kg	> 3160 mg/kg
2-butoxyethanol	450 ppm	530 mg/kg	400 - 500 mg/kg
Carbon dioxide	N/Av	N/Av (gas)	N/Av (gas)
1,3,5-Trimethylbenzene	24,000mg/m ³	23,000 mg/kg	N/Av
Xylene	6350 ppm	4300 mg/kg	> 5 mL/kg

Carcinogenic status	: Contains 2-Butoxyethanol. 2-Butoxyethanol is classified as a confirmed animal carcinogen by ACGIH (Group A3). No other components are classified as carcinogenic by IARC, ACGIH, OSHA or NTP.
Reproductive effects	: Not expected to cause reproductive effects.
Teratogenicity	: This product contains Xylene. Xylene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data.
Mutagenicity	: Not expected to be mutagenic in humans.
Epidemiology	: None known or reported by the manufacturer.

- Sensitization to material** : Not expected to be a skin or respiratory sensitizer.
- Synergistic materials** : None known or reported by the manufacturer.
- other important hazards** : CNS depression may result from extreme exposures.
- Conditions aggravated by overexposure** : None known or reported by the manufacturer.


SECTION 12 - ECOLOGICAL INFORMATION

- Ecotoxicity** : The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
- Mobility** : No data is available on the product itself.
- Persistence** : No data is available on the product itself.
- Bioaccumulation potential** : No data is available on the product itself.
- Other Adverse Environmental effects** : No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Do not puncture or incinerate containers.
- Methods of Disposal** : Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	none	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDGR, refer to Section 1.17 for additional exemption information, if shipping under this exemption.				

SECTION 15 - REGULATORY INFORMATION

Labelling:

WARNING! Flammable aerosol. Contents under pressure. Container may explode if heated.
 POISON! May be fatal if inhaled. Harmful or fatal if absorbed through the skin. May be harmful or fatal if swallowed in large amounts. May cause respiratory irritation. May cause nausea, vomiting, headache and other central nervous system effects. Material is an aspiration hazard. Can enter the lungs and cause damage. Causes skin and eye irritation. Contains material which can cause damage to the blood system, the liver and the kidneys. Possible birth defect hazard - contains material that may cause birth defects, based on animal data. Possible cancer hazard - contains material which may cause cancer.

PRECAUTIONS: Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. No sparking tools should be used. Avoid contact with incompatible materials. Do not puncture or incinerate containers. Wash thoroughly after handling. Store in a cool, dry, well-ventilated area away from sources of heat, ignition and sunlight

FIRST AID: If inhaled, move to fresh air. If breathing stopped, begin artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. For skin contact, immediately remove contaminated clothing then wash thoroughly with soap and water for at least 15 minutes. For eye contact, flush with running water for at least 15 minutes. If ingested, do not induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Never give anything by mouth to an unconscious person. For all cases, obtain medical attention immediately.

Refer To Material Safety Data Sheet for further information.

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.


This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

SECTION 16 - OTHER INFORMATION

- Legend** :
- ACGIH: American Conference of Governmental Industrial Hygienists
 - CAS: Chemical Abstract Services
 - CNS: Central Nervous System
 - HSDB: Hazardous Substances Data Bank
 - IARC: International Agency for Research on Cancer
 - Inh: Inhalation
 - LC: Lethal Concentration
 - LD: Lethal Dose
 - MSHA: Mine Safety and Health Administration
 - N/Ap: Not Applicable
 - N/Av: Not Available
 - NIOSH: National Institute of Occupational Safety and Health
 - NTP: National Toxicology Program
 - OSHA: Occupational Safety and Health Administration
 - PEL: Permissible exposure limit
 - RTECS: Registry of Toxic Effects of Chemical Substances
 - STEL: Short Term Exposure Limit
 - TCC: Tagliabue Closed Cup
 - TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 - TLV: Threshold Limit Values
 - TWA: Time Weighted Average
 - WHMIS: Workplace Hazardous Materials Identification System
- References** :
1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2010.
 2. International Agency for Research on Cancer Monographs, searched 2010.
 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2010 (Chempendium, HSDB and RTECs).
 4. Material Safety Data Sheets from manufacturer.

<p><u>Prepared for:</u> Radiator Specialty Co. of Canada 1711 Aimco Blvd. Mississauga, ON, Canada, L4W 1H7 Telephone: 905-625-9117 (Mon. - Fri., 9 AM - 5 PM) Please direct all enquiries to Radiator Specialty.</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	 <p>The Compliance Center Inc. HAZARDOUS MATERIALS REGULATIONS SPECIALISTS</p>

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

LIQUID WRENCH LUBRICANT

L212C

MSDS Revision Date (mm/dd/yyyy): 08/04/2010

Page 7 of 7

MSDS Preparation Date (mm/dd/yyyy)

: 08/01/2007

MSDS Revision Date (mm/dd/yyyy)

: 08/04/2010

Revision No.

: 2

Revision Information

: Sections 2 and 3, switched.

(M)SDS sections updated:

- 2. HAZARDS IDENTIFICATION;
- 3. COMPOSITION/INFORMATION ON INGREDIENTS;
- 5. FIRE-FIGHTING MEASURES;
- 8. EXPOSURE CONTROLS / PERSONAL PROTECTION;
- 9. PHYSICAL AND CHEMICAL PROPERTIES;
- 11. TOXICOLOGICAL INFORMATION;
- 12. ECOLOGICAL INFORMATION;
- 15. REGULATORY INFORMATION.

END OF DOCUMENT