

# **OSHA-Required Health And Safety Information!**

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

MATERIAL

SAFETY CRMATION

**SERVICE** 

#### Section 1

## MATERIAL SAFETY DATA SHEET # 17 Sizzle®

|   |  |  | HENOOLED            |  |  |  |
|---|--|--|---------------------|--|--|--|
| Date Prepared: 1/31/1990 Last Reviewed  | d: 1/31/1990 Last Reviewed: 10/10/2005 |  |                     | Hercules Chemical Company Inc.<br>111 South Street |  |  |
| Meets OSHA 29 CFR 1910.1200   |  | Passaic NJ 07055<br>Phone (800) 221-9330<br>Fax (800) 333-3456 |                     |  |  |  |
| Section 2 - Hazardous Ingredients/Identity Info   | rmation                                |  |                     |  |  |  |
| zardous Components (Specific Chemical Identity;<br>mmon Name(s), CAS Numbers)            OSHA PEL    ACGIH TI |  | ACGIH TLV  | Other Limits        | Upper Bound<br>Limit if SARA                       |  |  |
| This product is not for consumer use or sale. For   | professional use                       | e only. Replace o  | cap after use.      | Reportable   |  |  |
| Hydrochloric Acid (7647-01-0)   | 5ppm<br>(7mg/m³)                       | 5ppm<br>(7mg/m³)   | N/A<br>IDLH: 50 ppm | 31%  |  |  |

### HMIS Hazard Rating: Health: 3 Flammability: 0 Reactivity: 2 Personal Protection: H

| Section 3 - Physical/C | Chemical Characteristic                  | s                              |                             |                           |  |
|------------------------|--|--------------------------------|-----------------------------|---------------------------|--|
| Boiling Point (°F):    |  | Specific Gravity<br>(H2O = 1): | Vapor Density<br>(Air = 1): | Vapor Pressur<br>(mm Hg): |  |
| 181                    |  | 1.14 to 1.16                   | 1.27                        | 35                        |  |
| Melting Point (° F)    | Evaporation Rate:<br>(Butyl Acetate = 1) | Solubility in Water:           |                             |                           |  |
| N/A                    | >1                                       | Completely soluble             |                             |                           |  |
| Appearance And Color:  | Light yellow liquid                      |                                | Odor: Pungent,              | acid odor                 |  |
| Section 4 - Fire And   | Explosion Hazard Data                    |                                |                             |                           |  |
| Flash Point:           |  |                                | Flammable Limits            | LEL: UEL:                 |  |
| Not flammable          |  |                                | N/A                         |                           |  |

Extinguishing Media: For fires in the area use water, foam, dry chemical or CO2.

#### Special Firefighting Procedures:

Neutralize with chemically alkaline substances, such as soda ash or slaked lime to avoid formation of potentially explosive hydrogen gas. . Cool the containers with water if exposed to fire. Wear full protective clothing.

#### Unusual Fire And Explosion Hazards:

Contact with common metals may produce flammable, potentially explosive hydrogen gas. *Continued on Next Page* 

#### Section 5 - Reactivity Data Stability: Stable Conditions To Avoid: Do not store near or mix with strong alkalis such as sodium or potassium hydroxide. Incompatability Corrosive to most metals with evolution of hydrogen gas. May react with cyanides, sulfides or (Materials To Avoid): formaldehyde releasing toxic gases. Hazardous Decomposition: Hydrogen Chloride gas and Hydrogen Hazardous Polymerization: Will not occur Section 6 - Health Hazard Data Inhalation YES/Primary Routes of Entry Skin Yes/Primary Ingestion Yes/Secondary **Health Hazards**

Excessive contact can cause eye and skin burns. Ingestion causes severe burns to mouth, esophagus and stomach. Vapor extremely irritating.

Carcinogenicity NTP NO IARC NO OSHA Regulated NO

#### Signs And Symptoms of Exposure:

Irritation of eyes and skin. Inhalation of fumes may result in coughing and choking sensation.

#### Medical Conditions Generally Aggravated By Exposure:

INGESTION: Severe damage to internal organs (esophagus & pylorus) will occur if swallowed in large quantities. INHALATION: Fumes from product can cause injury to respiratory tract. Severe exposure can cause lung damage. SKIN CONTACT: Prolonged contact causes burns, skin irritation with discomfort and rash. EYE CONTACT: Will cause eye burn and irritation with discomfort, tearing or blurring of vision.

#### Emergency And First Aid Procedures:

INGESTION: Do not induce vomiting. If conscious, dilute by giving large quantities of water or milk. Do not give carbonates. Call a physician immediately. INHALATION: If excess fumes from the product are inhaled remove to fresh air. If not breathing give artificial respiration preferably mouth to mouth. If breathing is difficult give oxygen. Call a physician. SKIN CONTACT: Wash affected skin area with soapy water. Remove contaminated clothing. If burn/rash appears consult a physician immediately. EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Consult a physician immediately.

Continued on Next Page

| Section 7 - Precautions For Safe Handling And Use:   |   |  |  |  |  |
|--|---|--|--|--|--|
| Steps To Be Taken In Case Material Is Released Or Spilled:   |   |  |  |  |  |
| Evacuate area; keep upwind until gas has dispersed. If necessary apparatus & full protective clothing including boots. Dike large spi Ash. Comply with federal, state & local regulations. |   |  |  |  |  |
| Waste Disposal Method:   |   |  |  |  |  |
| Flush thoroughly with water applied to entire spill. Large spill: Wa before discharging to sewer.  | shing should be neutralized with lime/soda ash      |  |  |  |  |
| Precautions To Be Taken In Handling And Storing:   |   |  |  |  |  |
| Keep container tightly closed, away from heat, sparks & flame. K formaldehydes. Protect containers from damage.  | eep in cool place. Do not mix cyanides, sulfides or |  |  |  |  |
| Other Precautions:   |   |  |  |  |  |
| Store container out of sun and away from heat. Never use pressu  | re to empty containers.                             |  |  |  |  |
| Section 8 - Control Measures:  |   |  |  |  |  |
| Respiratory Protection:<br>Self-contained breathing apparatus or mask with canister for HCL  | fumes.  |  |  |  |  |
| Ventilation: Local Exhaust Maintain adequate ventilation.  | Special N/A   |  |  |  |  |
| Mechanical N/A   | Other: N/A  |  |  |  |  |
| Gloves: Long rubber or plastic gloves.   |   |  |  |  |  |
| Eye Protection: Chemical safety goggles and face shield.   |   |  |  |  |  |
| Other Protective<br>Clothing: Rubber apron, rubber boots, long sleeve shirts.  |   |  |  |  |  |
| Work/Hygienic Practice: Wash after use. Wash contacted clothing b  | before re-use.                                      |  |  |  |  |
| Additional Information:  |   |  |  |  |  |





AST!

For Hercules Material Safety Data Sheets by ACTS fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.