

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 71 Plumbers Caulk - Clear

Date Prepared: 9/21/1988 Last Reviewed: 2/23/2011

Meets OSHA 29 CFR 1910.1200



MATERIAL *SAFETY* FORMATION *SERVICE*

Hercules Chemical Company Inc. 111 South Street Passaic NJ 07055 Phone (800) 221-9330 Fax (800) 333-3456

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;

Common Name(s), CAS Numbers)

OSHA PEL ACGIH TLV **Other Limits**

Upper Bound Limit if SARA Reportable

ETHANEDIOL Cas #107-21-1

N/A

100mg/m³ AEROSOL FORM

ALKYLPHENOLETHOXYLATE Cas #9036-19-5

N/A

N/A

HMIS Hazard Rating: Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: A

Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):

Specific Gravity (H2O = 1):

Vapor Density (Air = 1):

Vapor Pressure

100°C; 212°F

1.05

N/A

(mm Hg): N/A

Melting Point (° F):

Evaporation Rate:

Solubility in Water:

N/A

(Butyl Acetate = 1) N/A

Unknown

VOC Level: 50.39

Appearance And Color:

Clear paste

Odor: Ammomia

Section 4 - Fire And Explosion Hazard Data

Flash Point:

Flammable Limits:

LEL:

UEL:

None

N/A

N/A

Extinguishing Media: As appropriate for surrounding fire.

Special Firefighting Procedures:

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

Unusual Fire And Explosion Hazards:

None

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable Conditions To Avoid: Unknown

Incompatability None known

(Materials To Avoid):

Hazardous Decomposition: CO, CO2 and nitrogen oxides (NOx); Toxic monomer fumes

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Routes of Entry: Inhalation YES Skin YES Ingestion NO EYES: YES

Health Hazards: Chronic Hazards:

Carcinogenicity: NTP NO IARC NO OSHA Regulated NO

Signs And Symptoms of Exposure:

Direct eye contact may cause irritation with redness, swelling, pain and tearing. Prolonged inhalation of vapors can cause irritation of the mouth, nose, throat and mucous membranes. Overexposure may cause headache, dizziness, tiredness, nausea and vomiting. May cause central nervous system effects. Causes skin irritation, skin defatting. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea

Medical Conditions Generally Aggravated By Exposure:

None known

Emergency And First Aid Procedures:

SKIN: Wash with soap and warm water. EYES: Flush with water for 15 minutes. Seek medical attention if irritation persists. INGESTION: Do not induce vomiting. If victim is conscious, give 2-4 glasses of water. Never give anything by mouth to someone unconscious. Seek medical attention immediately. INHALATION: Move to fresh air. If not breathing, give artificial respiration.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:

Steps To Be Taken In Case Material Is Released Or Spilled:

Use an absorbent material and sweep up for disposal

Waste Disposal Method:

Small quantities: non-hazardous landfill. Large quantities: Conform to federal, state and local regulations.

Precautions To Be Taken In Handling And Storing:

Store away from heat, sources of ignition and incompatibles

Other Precautions:

Keep out of reach of children.

Section 8 - Control Measures:

Respiratory Protection:

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Ventilation: Local Exhaust Adequate. Special N/A

Mechanical N/A Other: N/A

Gloves: Impervious gloves such as Neopren

Eye Protection: Monogoggles or Safety glasses.

Other Protective

Clothing: None necessary

Work/Hygienic Practices Use good personal hygiene practices.

Additional Information:





For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.